



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. ALBALOY PLATING (COPPER-TIN-ZINC) PL. 80 MIN. THICK
3. BERYLLIUM COPPER PER QQ-C-530
4. SILVER PL. 200 MIN. THICK OVER COPPER STRIKE
5. TEFLON MIL-P-19468
6. BLUE, PER PANTONE 3005C
7. JIS H 3250, C 2600

8	COVER	PE	NOTE 6	1	7166141A1-9	
7	FERRULE		NOTE 7	NOTE 2	1	FR-124/112X158
6	CONTACT PIN		NOTE 1	NOTE 4	1	7166511A1-6-305/24
5	BODY		NOTE 1	NOTE 2	1	7166111A2-5-B
4	GASKET	SILICONE	RED		1	GS-215/183XD16
3	CONTACT PIN		NOTE 3	NOTE 4	1	7166511A1-3-305/172-B
2	INSULATOR		NOTE 5	NATURAL	1	7161111A1-2T-214U
1	BARREL		NOTE 1	NOTE 2	1	7166511A1-1-93/74-B
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE
0.5-6 = ±0.2				<i>Andy. C</i>	07-09-03'
6-30 = ±0.4				CHECKED	DATE
30-120 = ±0.6				<i>Andy. C</i>	07-09-03'
120-315 = ±1				DRAWN	DATE
315-1000 = ±1.6				<i>Jayce. Y</i>	07-09-03'
1000-2000 = ±2.4				FILE NO.	F:\DWG\716\6111A1\214U-50\ATS

Amphenol	
Danbury,CT,USA-Tainan,Taiwan-Shenzhen,China	
TITLE	7/16 CRIMP JACK
DRAWING NO.	7166111A1-ATS-214U-50
ITEM NO.	076111AAD24AB5F