

REVISIONS											
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE									

  

3/8-32UNEF-2B

11 HEX

23.7 REF.

7.9

9.3

12.5

9.3

7.4

9.3

12.5

RECOMMENDED CABLE STRIPPING DIM'S  
(建議剝線尺寸)

4 0.9 8.3

  

15.5

0.8

1.4

2.1

15.8

10.9

12.4

  

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- JIS H 3250, C 2700

- CRIMPED FERRULE  
HEX CRIMP SIZE .429"
- CRIMPED CONTACT PIN  
HEX CRIMP SIZE .068"

  
  

6	FERRULE	NOTE 4	NOTE 2	1	FR-124/109X158	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				PART NO.		<h2 style="margin: 0;">Amphenol - Kai Jack</h2> <p style="margin: 0;">TAINAN TAIWAN</p> <h3 style="margin: 0;">F CRIMP PLUG</h3>			
5	CONTACT PIN	NOTE 1	NOTE 3	1	F1121A2-5-21/14					APPROVED					
4	BODY	NOTE 1	NOTE 2	1	FP-5CFB-K-4-B	CHECKED		DATE		DRAWING NO.					
3	INSULATOR	DELRIN	NATURAL	1	FP-5CFB-K-3-A	DRAWN		DATE		FILE NO.					
2	BARREL	NOTE 1	NOTE 2	1	F1121A2-2-93/74	SCALE		ISSUE		A					
1	SHELL	NOTE 1	NOTE 2	1	FP-5CFB-K-1-A	3/1		A							
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE		ISSUE		A					

394