



REMARK:1. NO.2 MUST WITHSTAND A 4 lbs. MIN. PUSHOUT FORCE FROM NO.1 AFTER STAKING OPERATION
 2. REMARK 1 IS MAINTAINED BY STAMPING THE FOUR POINTS SHOWN ON THE DRAWING WITHOUT PUNCTURING NO.1

STAKE IN 4 PLACES EQUALLY SPACED 90° APART (SEE REMARK 1,2)

PCB MOUNTING HOLES

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
- 1. BRASS PER QQ-B-626
 - 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 - 3. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 - 4. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS				PART NO. SMB1251M1-3GT30G-75	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED	DATE 10-11-01'
				CHECKED	DATE 10-11-01'
				DRAWN	DATE 10-11-01'
				SCALE	FILE NO.

Amphenol	
TITLE SMB P.C. MOUNT JACK	
DRAWING NO. KJ-SMB1251M1-3GT30G-75	
ITEM NO.	

3	CONTACT PIN	NOTE 1	NOTE 3	1	SMB1251M1-3-75
2	INSULATOR	NOTE 4	NATURAL	1	SMB1251M1-2T-75
1	BODY	NOTE 1	NOTE 2	1	SMB1251M1-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.