



業務部

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BERYLLIUM COPPER PER QQ-C-530
3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468

1. CRIMPED FERRULE
HEX CRIMP SIZE .128"

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A	PART NO.	TITLE
6	NUT		NOTE 1	NOTE 3	1	123-JACK-SN				Amphenol - Kai Jack TAINAN TAIWAN TITLE 1.0/2.3 CRIMP JACK (FOR RG-179/U, 187A/U) DRAWING NO. KJ-1236421A1-N/3GT30G-179U-75 FILE NO. F:\DWG\123\6421A1\179U-75\N3GT30G	
5	FERRULE	COPPER	NOTE 3	NOTE 3	1	FR-38/3X7C					
4	CONTACT PIN		NOTE 2	NOTE 5	1	1236421A1-4-11/06-75					
3	BARREL		NOTE 1	NOTE 3	1	SMB6121A1-4-23/17-C					
2	INSULATOR		NOTE 6	NATURAL	1	1236421A1-2T-5C					
1	BODY		NOTE 1	NOTE 4	1	1236421A1-1					
						DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED <i>[Signature]</i> DATE 03-03-00' CHECKED <i>[Signature]</i> DATE 03-03-00' DRAWN <i>[Signature]</i> DATE 03-03-00'	