



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. BRASS PER QQ-B-613
3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 80 MIN. THICK OVER COPPER STRIKE
6. TEFLON MIL-P-19468

- REMARK: 1. INSULATOR SHALL WITHSTAND AN 12 LB AXIAL FORCE APPLIED IN DIRECTION SHOWN WITH NO EVIDENCE OF MOVEMENT.  
(絕緣體至少需承受 12 磅的圖示方向推出力量且不可移動)
2. WHEN CRIMPING CONTACT PIN TO CABLE, CRIMP WITH AMPHENOL TOOL 227-944 (M22520/5-01) AND DIE SET 227-1221-09, CAVITY 'B' (M22520/5-09, CLOSURE 'B')(OR CTL-2, .068 HEX)  
(內導體壓著工具)
3. WHEN CRIMPING FERRULE TO CABLE, CRIMP WITH AMPHENOL TOOL 277-944 (M22520/5-01) AND DIE SET 227-1221-09 CAVITY 'A' (M22520/5-09, CLOSURE 'A')(OR CTL-2, .178 HEX)  
(套管壓著工具)
4. USE WITH BELDEN 8218, 1406A, 1164A, 1167A, 1418A, 1407A, 1417A CABLES, AND AT&T 735A, CLARK CV75SM CABLES.  
(適用纜線)

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	3/1	ISSUE	A2	FILE NO.	F:\DWG\CNPD\31\71033\00-A2	
8	FERRULE	COPPER	NOTE 3	1	31-1357-1	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				PART NO.		
7	CONTACT PIN	NOTE 1	NOTE 5	1	31-12774-2					APPROVED	<i>Mark C</i>	DATE 04-15-03'
6	SHELL	NOTE 1	NOTE 3	1	31-1500-C					CHECKED	<i>Karl J</i>	DATE 04-15-03'
5	GASKET	SILICONE	RED	1	82-1535-3					DRAWN	<i>Angela W</i>	DATE 04-15-03'
4	SPRING	SK5	NOTE 4	1	B50000-6							
3	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08							
2	INSULATOR	NOTE 6	NATURAL	1	31-12756							
1	BODY	NOTE 1	NOTE 3	1	31-12088-3							

**Amphenol**  
Danbury, CT, USA - Tainan, Taiwan - Shenzhen, China

TITLE  
BNC PLUG  
(FOR RGB AND SVHS CABLE)

DRAWING NO.  
31-71033

ITEM NO.  
31-71033

7AD-DR 17937 8