



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. SILVER PL. 120 MIN. THICK OVER COPPER STRIKE
 3. SILVER PL. 200 MIN. THICK OVER COPPER STRIKE
 4. TEFLON MIL-P-19468
 5. JIS H 3250, C 2700

10	FERRULE	NOTE 5	NOTE 2	1	FR-124/109X158
9	GASKET	SILICONE	BLACK	1	GS-101/65XD18
8	COVER	NOTE 1	NOTE 2	1	7161142A1-13
7	SHELL	NOTE 1	NOTE 2	1	7161141A1-7
6	GASKET	SILICONE	RED	1	GS-25/205X35
5	CONTACT BODY	NOTE 1	NOTE 2	1	7161141A1-5
4	GASKET	SILICONE	RED	1	GS-24/22XD1
3	CONTACT PIN	NOTE 1	NOTE 3	1	7161142A1-3-3/8
2	INSULATOR	NOTE 4	NATURAL	1	7161142A1-2T-3/8
1	BODY WITH BARREL	NOTE 1	NOTE 2	1	7161112A1-1S-93/74
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO.	7161112A1-120STS-7C-50
UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED	DATE
0.5-6	= ±0.2			10-11-01'
6-30	= ±0.4		CHECKED	DATE
30-120	= ±0.6			10-11-01'
120-315	= ±1		DRAWN	DATE
315-1000	= ±1.6			10-11-01'
1000-2000	= ±2.4		FILE NO.	

1. CRIMPED FERRULE
 HEX CRIMP SIZE .429"
 2. CONTACT PIN TO SOLDER

Amphenol

TITLE 7/16 R/A CRIMP PLUG
 (FOR RG-213/U, LMR 400, BELDEN 9913)

DRAWING NO.
 KJ-7161112A1-120STS-LMR400-50

ITEM NO.