


RECOMMENDED
CABLE STRIPPING DIM'S
(建議剝線尺寸)



RECOMMENDED
MOUNTING HOLE
(建議架設孔)

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. ALBALOY PLATING (COPPER-TIN-ZINC) PL. 80 MIN. THICK
 3. BERYLLIUM COPPER PER QQ-C-530
 4. SILVER PL. 200 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468
 6. BLUE, PER PANTONE 3005C
 7. JIS H 3250, C 2600

1. CRIMPED FERRULE
HEX CRIMP SIZE .429"
2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
10	SPANNER NUT			1	ST00AAE01A
9	FERRULE			1	FR-124/109X158
8	COVER	PE		1	7166141A1-9
7	GASKET	N. B. R.	BLACK	1	GS-415/355XD3
6	POST			1	PS00ABA01A
5	BARREL			1	7161111A2-1-93 /74-B
4	GASKET	SILICONE	RED	1	GS-215/183XD16
3	CONTACT PIN			1	7166411A1-3 -39/29
2	INSULATOR		NATURAL	1	7161111A1-2T -L400
1	BODY			1	7166411A1-1

DIMENSIONS ARE IN MILLIMETERS		PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVED	DATE
0.5-6 = ±0.2			12-18-02'
6-30 = ±0.4		CHECKED	DATE
30-120 = ±0.6			12-18-02'
120-315 = ±1		DRAWN	DATE
315-1000 = ±1.6		JOYCE	12-18-02'
1000-2000 = ±2.4			
SCALE 1.5/1	ISSUE A1	FILE NO.	F:\DWG\716\6411A1\9913\ATS

Amphenol

Danbury,CT,USA-Tainan,Taiwan-Shenzhen,China

TITLE 7/16 BULKHEAD CRIMP JACK
(FOR LMR400, BELDEN 9913, 9914)

DRAWING NO. 7166411A1-ATS-9913-50

ITEM NO.