



RECOMMENDED  
CABLE STRIPPING DIM'S  
(建議剝線尺寸)



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS PER QQ-B-626  
 2. BRASS PER QQ-B-613  
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE  
 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 6. JIS H 3250, C 2700

1. CRIMPED FERRULE  
HEX CRIMP SIZE .178"  
 2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
11	NUT			1	B5291-14
10	FERRULE			1	FR-51/445X127
9	WASHER			1	WS-128/9X08
8	SPRING	SK5		2	B50000-6
7	RETAINER RING			1	B50000-5
6	GASKET	RUBBER	RED	1	GS-115/BX15
5	CONTACT PIN			1	B5091-6-75-B
4	INSULATOR	DELTRIN	NATURAL	1	B5091-5-75
3	BARREL			1	B5091-3-38/27
2	HOUSING			1	B5091-2
1	SHELL			1	B50000-1-B

DIMENSIONS ARE IN MILLIMETERS  
 UNLESS OTHERWISE SPECIFIED TOLERANCES  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

PART NO.	
APPROVED	DATE 09-25-00'
CHECKED	DATE 09-25-00'
DRAWN	DATE 09-25-00'

<b>Amphenol - Kai Jack</b> TAINAN TAIWAN	
TITLE BNC R/A CRIMP PLUG (FOR BELDEN 8218), 2.5C2V)	
DRAWING NO. KJ-B1112A1-ND3G-8218-75	
FILE NO. F:\DWG\B\1112A1\8218-75\ND3G	