

REVISIONS					ISS		ZONE		DESCRIPTION\PER REQUEST\DATE	

FORMING

Ø14.5

25 REF.

Ø5.2

Ø6.85

RECOMMENDED CABLE STRIPPING DIM'S

4

3.7

8.3

Ø2.1

Ø0.9

Ø2.5

12.4

8

12.7

Ø8.5

Ø9.5

9

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- BRASS PER QQ-B-613
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
- GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- JIS H 3250, C 2700

9	FERRULE	NOTE 6	NOTE 3	1	FR-95/85X127
8	CONTACT PIN	NOTE 1	NOTE 5	1	B50000-8-25/09
7	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
6	SPRING	SK5	NOTE 4	1	B50000-6
5	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
4	GASKET	RUBBER	RED	1	GS-115/8X15
3	INSULATOR	DELTRIN	NATURAL	1	B50000-3-75-A
2	BODY	NOTE 1	NOTE 3	1	B50000-2-685/52
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B

DIMENSIONS ARE IN MILLIMETERS		
UNLESS OTHERWISE SPECIFIED TOLERANCES		
0.5-6	=	±0.2
6-30	=	±0.4
30-120	=	±0.6
120-315	=	±1
315-1000	=	±1.6
1000-2000	=	±2.4
SCALE	3/1	ISSUE A

PART NO.	
APPROVED	<i>Mark C</i> DATE 04-20-99'
CHECKED	<i>Mark C</i> DATE 04-20-99'
DRAWN	<i>Ala</i> DATE 04-20-99'

<p>KAI JACK INDUSTRIAL CO., LTD. TAINAN TAIWAN R.O.C.</p>	
TITLE	BNC CRIMP PLUG
DRAWING NO.	KJ-B1121A1-ND3G-8281-75
FILE NO.	F:\DWG\B\1121A1\8281-75\ND3G

業務部

88.4.21
& D

8825318