



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. NICKEL PL. 200 MIN. THICK OVER COPPER STRIKE
 5. SILVER PL. 80 MIN. THICK OVER COPPER STRIKE
 6. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 7. TEFLON MIL-P-19468

11	HEX NUT	NOTE 1	NOTE 3	1	B5210-11-11/64
10	BARREL	NOTE 1	NOTE 5	1	B5210-10-44/39
9	INSULATOR	NOTE 7	NATURAL	1	B5210-9T-50
8	CONTACT PIN	NOTE 1	NOTE 6	1	B5210-8-21/12
7	INSULATOR	DELTRIN	NATURAL	1	B5210-7-50
6	WASHER	NOTE 2	NOTE 3	1	WS-128/9X08
5	SPRING	SK5	NOTE 4	1	B50000-6
4	RETAINER RING	NOTE 1	NOTE 3	1	B50000-5
3	GASKET	RUBBER	RED	1	GS-115/BX15
2	BODY	NOTE 1	NOTE 3	1	B5200-2-A
1	SHELL	NOTE 1	NOTE 3	1	B50000-1-B
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS			PART NO. B1141G1-ND3G-3-50	
UNLESS OTHERWISE SPECIFIED TOLERANCES			APPROVED	DATE
0.5-6	= ±0.2			10-11-01'
6-30	= ±0.4		CHECKED	DATE
30-120	= ±0.6			10-11-01'
120-315	= ±1		DRAWN	DATE
315-1000	= ±1.6			10-11-01'
1000-2000	= ±2.4			
SCALE	3/1	ISSUE	FILE NO.	

Amphenol

TITLE
BNC CLAMP PLUG

DRAWING NO.
KJ-B1141G1-ND3G-59U-50

ITEM NO.

1. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"
OR CONTACT PIN TO SOLDER