

REVISIONS				
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE		
B	A-1	NO.1 WAS CHANGED\RD-DM89062301C\06-23-00'		
		NO.6 WAS CHANGED\RD-DM89060902C\06-09-00'		
C	A-1	NO.4 WAS CHANGED\RD-DM89100201Y\10-02-00'		
D	A-1	NO.1 WAS CHANGED\RD-DM89121901C\12-19-00'		
	C-2	DELETED "ROLLING"\RD-DM89121901C\12-19-00'		

REMARK:1. AMONG NO.1, NO.5 AND NO.6 MUST WITHSTAND 15 IN-LBS TORQUE AFTER STAKING OPERATION

2. REMARK 1 IS MAINTAINED BY STAKING SHOWN ON THE DRAWING WITHOUT PUNCTURING NO.5

(1. 打點後零件 1, 5, 6 之間至少須承受 15 吋一磅的扭力)

(2. 打點後除需符合備註 1 要求外 且不可擊穿零件 5)

STAKE IN 6 PLACES  
EQUALLY SPACED 60°  
APART  
(打六點 間隔 60°)  
(SEE REMARK 1,2)

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626

2. BRASS PER QQ-B-613

3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

4. PHOSPHOR BRONZE PER QQ-B-750

5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

出圖  
2000.12.27  
設計部

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	2.5/1	ISSUE	D
8	HEX NUT	NOTE 1	NOTE 3	1	HN16-1/2-28X28	DIMENSIONS ARE IN MILLIMETERS			
7	LOCK WASHER	NOTE 2	NOTE 3	1	LW-16/13X05	UNLESS OTHERWISE SPECIFIED TOLERANCES			
6	HOUSING	NOTE 1	NOTE 3	1	B7925-6-C	0.5-6 = ±0.2			
5	BODY	NOTE 1	NOTE 3	1	B7925-5	6-30 = ±0.4			
4	INSULATOR	DELTRIN	NATURAL	1	B7925-4-B	30-120 = ±0.6			
3	CONTACT PIN	NOTE 4	NOTE 5	1	B7900-4	120-315 = ±1			
2	INSULATOR	DELTRIN	NATURAL	2	B7996ZZ-3-75	315-1000 = ±1.6			
1	BODY	NOTE 1	NOTE 3	1	B7925-1-D	1000-2000 = ±2.4			

APPROVED *[Signature]* DATE 12-19-00'

CHECKED *[Signature]* DATE 12-19-00'

DRAWN *[Signature]* DATE 12-19-00'

**Amphenol - Kai Jack**  
TAINAN TAIWAN

TITLE  
BNC FEMALE TO FEMALE BULKHEAD  
ISOLATED ADAPTOR

DRAWING NO.  
KJ-B7771B1-ND3G-75

FILE NO. F:\DWG\B\7771B1\75\ND3G

RD-DR11721