



REMARK: 1. AMONG NO.1, NO.5 AND NO.6 MUST WITHSTAND 15 IN-LBS TORQUE AFTER STAKING OPERATION
 2. REMARK 1 IS MAINTAINED BY STAKING SHOWN ON THE DRAWING WITHOUT PUNCTURING NO.5
 (1. 打點後零件 1, 5, 6 之間至少須承受 15 吋一磅的扭力)
 (2. 打點後除需符合備註 1 要求外 且不可擊穿零件 5)

STAKE IN 6 PLACES EQUALLY SPACED 60° APART
 (打六點 間隔 60°)
 (SEE REMARK 1,2)

RECOMMENDED MOUNTING HOLE
 (建議架設孔)

STAMP (IF ANY)
 噴字 (若有要求)

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. PHOSPHOR BRONZE PER QQ-B-750
 5. GOLD PL. 10 MIN. OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. TEFLON MIL-P-19468

1. MAX. PANEL THICKNESS=4mm



NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	2.5/1	ISSUE	A1	FILE NO.	F:\DWG\B\7771B4\002\75\NT10G									
8	HEX NUT	NOTE 1	NOTE 3	1	HN16-1/2-28X28	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	PART NO.	APPROVED	DATE	05-05-03'	TITLE									
7	LOCK WASHER	NOTE 2	NOTE 3	1	LW-16/13X05							DRAWN	DATE	05-05-03'	DRAWING NO.					
6	HOUSING	NOTE 1	NOTE 3	1	B7925-6-C											ANGELA	DATE	05-05-03'	ITEM NO.	
5	BODY	NOTE 1	NOTE 3	1	B7925-5															1. MAX. PANEL THICKNESS=4mm
4	INSULATOR	DELRIN	NATURAL	1	B7925-4-B															
3	CONTACT PIN	NOTE 4	NOTE 5	1	B7771B4-3															
2	INSULATOR	NOTE 6	NATURAL	2	B7771B4-2T-75															
1	BODY	NOTE 1	NOTE 3	1	B7925-1-D															

Amphenol

Danbury, CT, USA - Tainan, Taiwan - Shenzhen, China

BNC FEMALE TO FEMALE BULKHEAD ISOLATED ADAPTOR

B7771B4-002-NT10G-75