



REMARK: 1. NO.5 CONTACT PIN SHALL WITHSTAND A FORCE OF 6 LBS. TOWARD THE FACE OF THE CONECTOR FROM CABLE ENTRY END.
 2. FORM NO.4 TO $\phi 7.75$ mM TO CAPTIVATE NO.3.
 3. NO.3 MUST WITHSTAND A 10 LBS. PUSHOUT FORCE FROM NO.4 AFTER FORM OVER OPERATION.

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
- BRASS PER QQ-B-626
 - BRASS PER QQ-B-613
 - NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 - BERYLLIUM COPPER PER QQ-C-530
 - GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 - TEFLON MIL-P-19468
 - JIS H 3250, C 2700



9	FERRULE	NOTE 7	NOTE 3	1	FR-39/32X95
8	GASKET	SILICONE	RED	1	GS-16/122X15S
7	HEX NUT	NOTE 1	NOTE 3	1	HN14-1/2-28X28
6	LOCK WASHER	NOTE 2	NOTE 3	1	LW-16/13X05
5	CONTACT PIN	NOTE 4	NOTE 5	1	B87101902-5
4	BARREL	NOTE 1	NOTE 3	1	456-118
3	INSULATOR	NOTE 6	NATURAL	1	B87101902-3
2	INSULATOR	NOTE 6	NATURAL	1	B87101902-2
1	BODY	NOTE 1	NOTE 3	1	B87101902-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED TOLERANCES
 0.5-6 = ± 0.2
 6-30 = ± 0.4
 30-120 = ± 0.6
 120-315 = ± 1
 315-1000 = ± 1.6
 1000-2000 = ± 2.4

PART NO.		DATE	
APPROVED		10-26-98'	
CHECKED		10-26-98'	
DRAWN		10-26-98'	
SCALE	2.5/1	ISSUE	A

KAI JACK INDUSTRIAL CO., LTD.
 TAINAN TAIWAN R.O.C.

TITLE: BNC BULKHEAD CRIMP JACK

DRAWING NO. B87101902-NT30G

FILE NO. F:\DWG\B\87101902\NT30G

F
E
D
C
B
A

F
E
D
C
B
A

1 2 3 4 5 6 7 8