



業務部

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. BERYLLIUM COPPER PER QQ-C-530
 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. TEFLON MIL-P-19468

ACCEPTS ø0.5~1.05 CENTER CONDUCTOR TYPICAL
 (接受ø0.5~1.05的中心導針)



NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
9	HEX NUT			2	HN11-3/8-32X21
8	LOCK WASHER			1	LW-127/97X05
7	INSULATOR		NATURAL	1	F6252A1-006-7
6	CONTACT PIN			1	F6252A1-006-6
5	INSULATOR		NATURAL	1	F6351A1-2
4	CONTACT PIN			1	F6252A1-006-4
3	INSULATOR		NATURAL	1	F6252A1-006-3
2	BODY			1	F6252A1-006-2
1	HOUSING			1	F6252A1-006-1

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED TOLERANCES
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

PART NO.	
APPROVED	DATE
CHECKED	DATE
DRAWN	DATE

Amphenol - Kai Jack	
TAINAN TAIWAN	
TITLE	
F R/A P.C. MOUNT JACK	
DRAWING NO.	
KJ-F6252A1-006-NT3G-75	
FILE NO. F:\DWG\F\6252A1\006\75\NT3G	

RDR DR 11216