



RECOMMENDED  
CABLE STRIPPING DIM'S

1. CRIMPED FERRULE  
HEX CRIMP SIZE .128"  
2. CONTACT PIN TO SOLDER

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. BRASS PER QQ-B-613
  3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  4. BERYLLIUM COPPER PER QQ-C-530
  5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  6. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS  
UNLESS OTHERWISE SPECIFIED TOLERANCES

0.5-6	= ±0.2
6-30	= ±0.4
30-120	= ±0.6
120-315	= ±1
315-1000	= ±1.6
1000-2000	= ±2.4

PART NO.	MCX1112A1-NT30G-6-75
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'

**Amphenol**

TITLE MCX R/A CRIMP PLUG  
(FOR RG-179/U,187A/U)

DRAWING NO. KJ-MCX1112A1-NT30G-179U-75

ITEM NO.

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
7	FERRULE	COPPER	NOTE 3	1	FR-38/3X7C
6	COVER	NOTE 2	NOTE 3	1	CV-405X08-T
5	INSULATOR	DELTRIN	NATURAL	1	MCX1112A1-5
4	CONTACT PIN	NOTE 1	NOTE 5	1	MCX1112A1-4S-75
3	INSULATOR	NOTE 6	NATURAL	1	MCX1112A1-3T-75-B
2	BODY	NOTE 4	NOTE 3	1	BD08AAN01E
1	HOUSING	NOTE 1	NOTE 3	1	MCX1112A1-1-23/17-D