



業務部

RECOMMENDED
CABLE STRIPPING DIM'S

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
- 1. BRASS PER QQ-B-626
 - 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 - 3. NICKEL PL. 100 MIN. THICK OVER COPPER PL. 300 MIN. THICK
 - 4. PHOSPHOR BRONZE PER QQ-B-750
 - 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

出圖
87.9.07
R&D

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
5	FERRULE	COPPER	NOTE 2	1	FR-648/533X 127C
4	CONTACT PIN	NOTE 4	NOTE 5	1	MU6121F1-4-21/ 09
3	INSULATOR	DELRI	NATURAL	1	MU6121F1-3-50 -B
2	BARREL	NOTE 1	NOTE 2	1	MU6121F1-2- 4E/31
1	BODY	DIECAST	NOTE 3	1	MU6121F1-1

DIMENSIONS ARE IN: MILLIMETERS	
UNLESS OTHERWISE SPECIFIED TOLERANCES	
0.5-6	= ±0.2
6-30	= ±0.4
30-120	= ±0.6
120-315	= ±1
315-1000	= ±1.6
1000-2000	= ±2.4

PART NO.	
APPROVED	DATE 09-04-98'
CHECKED	DATE 09-04-98'
DRAWN	DATE 09-04-98'

<p>KAI JACK INDUSTRIAL CO., LTD. TAINAN TAIWAN R.O.C.</p>	
TITLE MINI-UHF CRIMP JACK	
DRAWING NO. KJ-MU6121B1-ND3G-58U-50	
FILE NO. F:\DWG\MU\6121B1\58U-50\ND3G	

8MU-R0261