

KAI JACK INDUSTRIAL CO., LTD.

PRODUCT SPECIFICATION

DATE(日期): 91/09/26

SERIES(產品類別)	N CRIMP PLUG	PART NO.(圖號)	N1121A1-ST30GA-58U-50
MATERIAL AND FINISH(材質及表面處理)			
DESCRIPTION(名稱)		MATERIAL(材質)	FINISH(表面處理)
Center Contact(中心導體)		BRASS	30μ "GA
Insulator(絕緣體)		TEFLON	NATURAL
Outer Contact(外導體)		BRASS	80μ " SILVER
Others(其它)			
ELECTRICAL(電氣特性)			
Impedance(阻抗)		50 Ω	
Voltage Standing Wave Ratio(VSWR;駐波比)		N/A Max. - GHz	
Dielectric Withstanding Voltage(絕緣耐電壓)		2500 Volts Min. RMS	
Contact Resistance (導體阻抗)	Center Contact (中心導體)	3 mΩ Max.	
	Outer Contact (外導體)	2 mΩ Max.	
Insulation Resistance(絕緣阻抗)		5000 MΩ Min.	
MECHANICAL(機械特性)			
Force To Engage/Disengage(接合力 / 脫離力): 6 in-lbs. Max.			
Coupling Nut Retention(聯結螺帽承受力): 100 lbs. Min.			
Coupling Proof Torque(聯結螺帽承受扭力): 30 in-lbs. Min.			
Contact Retention(中心導體承受力): N/A			
Cable Retention(纜線承受力): 20 lbs. Min.			
REMARKS(備註)			

APPROVED:



REVIEWED:



DRAFTED:

