



業務部

RECOMMENDED
CABLE STRIPPING DIM'S

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED TOLERANCES
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
11	CONTACT PIN			1	N5201-11-35/29-C
10	NUT			1	B5201-12-19/111
9	WASHER			1	WS-16/115X05
8	GASKET	SILICONE	RED	1	B5201-10
7	BRAID CLAMP			1	B5201-9-111/91
6	WASHER			1	WS-145/75X05
5	INSULATOR		NATURAL	1	N5201-5T-50-9913
4	RETAINER RING	SUS 304	NATURAL	1	N5000-7-C
3	GASKET	SILICONE	RED	1	GS-156/8X15
2	BODY			1	N5201-2-19/111
1	SHELL			1	N5000-1-B

SCALE	2.5/1	ISSUE	A
APPROVED	Mark. C		DATE 07-07-98'
CHECKED	Mark. C		DATE 07-07-98'
DRAWN	alex.H		DATE 07-07-98'

KAI JACK INDUSTRIAL CO., LTD. TAINAN TAIWAN R.O.C.	
TITLE N CLAMP PLUG (FOR BELDEN 9913, 9914)	
DRAWING NO. KJ-N1141A2-NT3G-9913-50	
FILE NO. F:\DWG\N\1141A2\9913-50\NT3G	

出圖
87.7.13
R&D