



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. ALBALOY PLATING (COPPER-TIN-ZINC) PL. 80 MIN. THICK
 3. BERYLLIUM COPPER PER QQ-C-530
 4. GOLD PL. 30 MIN. THICK OVER COPPER PL. 100 MIN. THICK
 5. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS				PART NO.		
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE	
0.5-6 = ±0.2				A. J. C.	06-16-03'	
6-30 = ±0.4					CHECKED	DATE
30-120 = ±0.6					Ken	06-16-03'
120-315 = ±1						DRAWN
315-1000 = ±1.6				EMYA	06-16-03'	
1000-2000 = ±2.4					FILE NO.	F:\DWG\N6551A1\049\50\AT30GA

Amphenol Danbury, CT, USA - Tainan, Taiwan - Shenzhen, China	
DRAWING NO.	N6551A1-049-AT30GA-50
ITEM NO.	036551ADPO2AG5F

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
3	CONTACT PIN	NOTE 3	NOTE 4	1	CP03AGB02A
2	INSULATOR	NOTE 5	NATURAL	1	NS00ABJ43A
1	OUTER BODY WITH PANEL	NOTE 1	NOTE 2	1	172144-1S-E

SALES

ISSUED
 2003. 6. 20
 R & D