



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. PHOSPHOR BRONZE PER QQ-B-750
 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. TEFLON MIL-P-19468

| DIMENSIONS ARE IN MILLIMETERS | | | |
|---------------------------------------|--------|--|--|
| UNLESS OTHERWISE SPECIFIED TOLERANCES | | | |
| 0.5-6 | = ±0.2 | | |
| 6-30 | = ±0.4 | | |
| 30-120 | = ±0.6 | | |
| 120-315 | = ±1 | | |
| 315-1000 | = ±1.6 | | |
| 1000-2000 | = ±2.4 | | |

| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO. |
|-----|-------------|----------|---------|------|----------------|
| 7 | HEX NUT | | | 1 | HN19-5/8-24X31 |
| 6 | LOCK WASHER | | | 1 | LW-19/16X06 |
| 5 | GASKET | SILICONE | RED | 1 | GS-20/16X15 |
| 4 | BODY | | | 1 | N7910-4 |
| 3 | CONTACT PIN | | | 1 | N7900-3 |
| 2 | INSULATOR | | NATURAL | 1 | N7900-2T-50-B |
| 1 | HOUSING | | | 1 | N7910-1 |

| PART NO. | |
|----------|----------------|
| APPROVED | DATE 01-26-99' |
| CHECKED | DATE 01-26-99' |
| DRAWN | DATE 01-26-99' |

| KAI JACK INDUSTRIAL CO., LTD. TAINAN TAIWAN R.O.C. | |
|---|-------------------------------------|
| TITLE | N FEMALE TO FEMALE BULKHEAD ADAPTOR |
| DRAWING NO. | KJ-N7471A1-NT3G-50 |
| FILE NO. | F:\DWG\N\7471A1\50\NT3G |

參考
2000. 12. 14
設計部

88DFR472