



**SALES**

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS PER QQ-B-626  
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE  
 3. BERYLLIUM COPPER PER QQ-C-530  
 4. SILVER PL. 200 MIN. THICK OVER COPPER STRIKE  
 5. TEFLON MIL-P-19468  
 6. BLUE, PER PANTONE 3005C

ISSUED  
 2001.10.02  
 R&D

10	COVER	PE	NOTE 6	1	7166141A1-9	
9	CONTACT PIN		NOTE 3	NOTE 4	1	7167071A1-5-D
8	SHELL		NOTE 1	NOTE 2	1	N5000-1-B
7	GASKET	SILICONE	RED		1	GS-156/8X15
6	RETAINER RING	SUS304	NATURAL		1	N5000-7-C
5	OUTER CONTACT		NOTE 1	NOTE 2	1	7167071A1-2
4	CONTACT PIN		NOTE 1	NOTE 4	1	NM-716F-4-B
3	INSULATOR		NOTE 5	NATURAL	1	NM-716M-4T-50
2	BODY		NOTE 1	NOTE 2	1	NM-716M-3
1	HOUSING		NOTE 1	NOTE 2	1	NM-716F-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE
0.5-6 = ±0.2				<i>Dark C</i>	09-26-01'
6-30 = ±0.4				CHECKED	DATE
30-120 = ±0.6				<i>Andy C</i>	09-26-01'
120-315 = ±1				DRAWN	DATE
315-1000 = ±1.6				<i>Stalys w</i>	09-26-01'
1000-2000 = ±2.4				FILE NO. F:\DWG\NM\716F\50\NTS	

<b>Amphenol - Kai Jack</b>	
TAINAN TAIWAN	
TITLE	N MALE TO 7/16 FEMALE ADAPTOR
DRAWING NO.	KJ-NM-716F-NTS-50
ITEM NO.	03M-07F1-NJ-5-F

RDBDR12902