



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
  2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  3. PHOSPHOR BRONZE PER QQ-B-750
  4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  5. TEFLON MIL-P-19468
  6. JIS H 3250, C 2600

1. CRIMPED FERRULE  
HEX. CRIMP SIZE .213"
2. CRIMPED CONTACT PIN  
HEX. CRIMP SIZE .100"



NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
9	FERRULE			1	FR-635/S6X127
8	CONTACT PIN			1	RN1121A1-8-3/11
7	RETAINER RING	SUS 304	NATURAL	1	N5000-7-C
6	GASKET	SILICONE	RED	1	GS-156/8X15
5	CONTACT BODY			1	N5000-5
4	INSULATOR			1	N5000-4T-50-A
3	BARREL			1	N5000-3-427/32
2	BODY			1	N5000-2
1	SHELL			1	N5000-1-B

DIMENSIONS ARE IN MILLIMETERS				PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE
0.5-6	= ±0.2			<i>Galckey</i>	02-25-02'
6-30	= ±0.4			CHECKED	DATE
30-120	= ±0.6			<i>Galckey</i>	02-25-02'
120-315	= ±1			DRAWN	DATE
315-1000	= ±1.6			<i>Galckey</i>	02-25-02'
1000-2000	= ±2.4				
SCALE	2.5/1	ISSUE	A	FILE NO.	F:\DWG\RN\1121A1\223U-50\NT3G

Amphenol - Kai Jack	
TAINAN TAIWAN	
TITLE N REVERSE POLARITY CRIMP PLUG (FOR RG-55/U,142/U,223/U,400/U)	
DRAWING NO. KJ-RN1121A1-NT3G-223U-50	
ITEM NO. 531121AAB26NA5F	

7 PD-DR 1A16 8