



ISS	ZONE	REVISIONS	
ISS	ZONE	DESCRIPTION	PER REQUEST\DATE

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	FERRULE	NOTE 1	NOTE 2	1	FRO0ADM02A
5	BO-JY	NOTE 1	NOTE 2	1	
4	INSULATOR	NOTE 5	NATURAL	1	SMA6252A2-001-4
3	CONTACT PIN	NOTE 3	NOTE 4	1	
2	INSULATOR	NOTE 5	NATURAL	1	SMA5071A1-3T-50
1	HOUSING	NOTE 1	NOTE 2	1	

DIMENSIONS ARE IN MILLIMETERS			
UNLESS OTHERWISE SPECIFIED TOLERANCES			
0.5-6	=	±0.2	
6-30	=	±0.4	
30-120	=	±0.6	
120-315	=	±1	
315-1000	=	±1.6	
1000-2000	=	±2.4	

PART NO.	
APPROVED	DATE
CHECKED	DATE
DRAWN	DATE
FILE NO.	F:\DWG\SMA\6182U1\001\50\3GT50G

Amphenol - Kai Jack	
TAINAN TAIWAN	
TITLE	SMA R/A CRIMP JACK (FOR 1.13 AND 1.35 CABLE)
DRAWING NO.	SMA6182U1-001-3GT50G-50
ITEM NO.	

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. BERYLLIUM COPPER PER QQ-C-530
 4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468

CHAM. 30° TO MAX. DIA. ACROSS FLATS. (BOTH SIDES)
 (倒角 30° 至對邊平面之最大尺寸位置) (兩邊)

B VIEW
 (B 視圖)

RECOMMENDED CABLE STRIPPING DIM'S
 (建議剝線尺寸)

