



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

1. BRASS PER QQ-B-626
2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
3. BERYLLIUM COPPER PER QQ-C-530
4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
5. TEFLON MIL-P-19468

DIMENSIONS ARE IN MILLIMETERS					PART NO.				KAI JACK INDUSTRIAL CO., LTD. TAINAN TAIWAN R.O.C.			
5	RING	NOTE 1	NOTE 2	1	SMA7530-5-B	UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				APPROVED <i>Mark C</i> DATE 09-21-98'		TITLE SMA PANEL RECEPT. JACK
4	INSULATOR	NOTE 5	NATURAL	1	SMA7530-4T-50					CHECKED <i>Mark C</i> DATE 09-21-98'		DRAWING NO. KJ-SMA6551B1-NT50G-50
3	CONTACT PIN	NOTE 3	NOTE 4	1	SMA7530-3					DRAWN <i>Betty L</i> DATE 09-21-98'		FILE NO. F:\DWG\SMA\6551B1\50\NT50G
2	INSULATOR	NOTE 5	NATURAL	1	SMA7530-2T-50-B							
1	BODY	NOTE 1	NOTE 2	1	SMA7535-1-B							
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	5/1	ISSUE	A			

SMA-R13/6