



業務部

- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. BERYLLIUM COPPER PER QQ-C-530
 4. TEFLON MIL-P-19468
 5. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

出圖
2001.1.31
設計部

8	COVER	NOTE 2	NOTE 5	1	CV-5X05-T
7	RING	NOTE 1	NOTE 5	1	SMA7530-5-B
6	INSULATOR	NOTE 4	NATURAL	1	SMA7550-4T-50
5	CONTACT PIN	NOTE 1	NOTE 5	1	SMA6552E1-5
4	INSULATOR	NOTE 4	NATURAL	1	SMA7530-2T-50-B
3	INSULATOR	NOTE 4	NATURAL	1	SMA6252A2-3T-50-B
2	CONTACT PIN	NOTE 3	NOTE 5	1	SMA6552E1-2
1	HOUSING WITH BODY	NOTE 1	NOTE 6	1	SMA6552E1-1S

DIMENSIONS ARE IN MILLIMETERS
UNLESS OTHERWISE SPECIFIED TOLERANCES

0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

PART NO.	
APPROVED	DATE
CHECKED	DATE
DRAWN	DATE

Amphenol - Kai Jack	
TAINAN TAIWAN	
TITLE	
SMA R/A PANEL JACK	
DRAWING NO.	
KJ-SMA6552E1-NT50G-50	
FILE NO. F:\DWG\SMA\6552E1\50\NT50G	