

1	2		3	4	5	6	7	8		
REVISIONS										
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE								
<p>REMARK:1. NO.4 MUST WITHSTAND A 6 lbs. MIN. PUSHOUT FORCE FROM NO.2 AFTER STAKING OPERATION</p> <p>2. REMARK 1 IS MAINTAINED BY STAMPING THE FOUR POINTS SHOWN ON THE DRAWING WITHOUT PUNCTURING NO.1</p>										
<p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)</p> <p>1. BRASS PER QQ-B-626</p> <p>2. BERYLLIUM COPPER PER QQ-C-530</p> <p>3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>5. TEFLON MIL-P-19468</p>										
8	GASKET	SILICONE	RED	1	GS-6/43X06	PART NO. SMAM-MCXF1-3GT50G-50			<h1 style="text-align: center;">Amphenol</h1> <p style="text-align: center;">TITLE SMA MALE TO MCX FEMALE ADAPTOR</p> <p style="text-align: center;">DRAWING NO. KJ-SMAM-MCXF1-3GT50G-50</p> <p style="text-align: center;">ITEM NO.</p>	
7	RETAINER RING	NOTE 2	NATURAL	1	SMA5000-4-B	APPROVED DATE 10-11-01'				
6	BODY	NOTE 1	NOTE 3	1	SMAM-MCXF1-5-B	CHECKED DATE 10-11-01'				
5	CONTACT PIN	NOTE 2	NOTE 4	1	SMAM-MCXF1-4	DRAWN DATE 10-11-01'				
4	INSULATOR	NOTE 5	NATURAL	1	SMAM-MCXM1-3-B					
3	INSULATOR	NOTE 5	NATURAL	1	SMAF-MCXF1-2-B	DIMENSIONS ARE IN MILLIMETERS				
2	HOUSING	NOTE 1	NOTE 3	1	SMAM-SMBM1-2	UNLESS OTHERWISE SPECIFIED TOLERANCES				
1	SHELL	NOTE 1	NOTE 3	1	SMA5000-1-C	0.5-6 = ±0.2				
						6-30 = ±0.4				
						30-120 = ±0.6				
						120-315 = ±1				
						315-1000 = ±1.6				
						1000-2000 = ±2.4				
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A	FILE NO.

Amphenol

TITLE
SMA MALE TO MCX FEMALE ADAPTOR

DRAWING NO.
KJ-SMAM-MCXF1-3GT50G-50

ITEM NO.