



SPECIFICATIONS :

- 1.IMPEDANCE : 50 OHMS
- 2.GOLD :3 microinches OVER SUS303(BODY & CAP)
- 3.GOLD :3 microinches OVER BRASS(FERRULE)
- 4.GOLD :30 microinches OVER BRASS(PIN)
- 5.SUCO PLATE FINISH :SUCO PLATE OVER P.Bronze(BODY & SHELL)
- 6.REMOVED ALL BURRS & BREAK ALL SHARP EDGES

CABLE GROUP	DWG. NO.	FERRULE NO.	ϕA	ϕB
FOR RG-58 CABLE	152-M050/149	000-X605-F0-BG	5.6	6.5
FOR RG-142/223 CABLE	152-M051/149	000-X608-F0-BG	5.9	6.7

9	ferrule	000-X60X-F0-BG	1	BRASS	GOLD
8	cap	132-M020-C0-SA	1	SUS303	GOLD
7	shell	152-M000-H0-BY	1	BRASS	SUCO PLATE(CuSnPb)
6	dielectric	101-M024-80-DX	1	PTFE	NONE
5	dielectric	152-M130-70-DX	1	PTFE	NONE
4	pin	152-M050-40-BC	1	BRASS	GOLD
3	body	152-M050-30-SA	1	SUS303	GOLD
2	body	152-M020-20-PY	1	PB	SUCO PLATE(CuSnPb)
1	body	152-M050-10-SA	1	SUS303	GOLD
ITEM	DESCRIPTION	PART NUMBER	QTY	MATERIAL	FINISH

REV	ECN NO.	NAME	DATE	TOLERANCE: DECIMALS: .XX ± 0.08 .X ± 0.13 DIAMETER: ± 0.03	 皇亮精密企業股份有限公司 HUANG LIANG PRECISION ENTERPRISE CO., LTD TITLE: QMA R/A PLUG FOR CABLE
A		CHEN	95/12/11		
Drawn: <i>CHEN</i> 95/12/11 Checked: <i>CHEN</i> 95/12/11 Approved: <i>H.T. Lin</i> 95/12/11 Unit: mm				M DWG.NO. 152-M050~M051/149	SCALE: 10/1 SHEET: 1 OF 1 SERIES: QMA
File Path: E:\CONNECTOR\QMA					