



REMARK: NO.2 MUST TURN AND SLIDE WITHOUT BINDING AND MUST BE CAPABLE OF WITHSTANDING A PULL-OFF FORCE OF 30 LBS. MIN. AFTER FORMING  
(NO.2 成型後可自由轉動和移動且至少需承受 30 LBS. 的拉力)

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS
- 2. PHOSPHOR BRONZE
- 3. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 50 MIN. THICK OVER COPPER PL. 50 MIN. THICK
- 4. ALBALOY PLATING (COPPER-TIN-ZINC) PL. 80 MIN. THICK
- 5. TEFLON

- 1. CRIMPED FERRULE
- 2. CONTACT PIN TO SOLDER

REVISIONS						DIMENSIONS ARE IN MILLIMETERS				PART NO.		TITLE QMA R/A CRIMP PLUG (FOR 8X, LMR-240 CABLE)	
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE				UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE		
						0.5-6 = ±0.2	6-30 = ±0.4	30-120 = ±0.6	120-315 = ±1	315-1000 = ±1.6	1000-2000 = ±2.4		05-06-'11
													05-06-'11
7	FERRULE	NOTE 1	NOTE 4	1	FR-66-75-127								
6	COVER	NOTE 1	NOTE 4	1	CV-523-06								
5	CONTACT PIN	NOTE 1	NOTE 3	1	700-1112A2-5								
4	INSULATOR	NOTE 5	NATURAL	1	700-1112A1-4T								
3	OUTER CONTACT	NOTE 2	NOTE 4	1	700-1000-2								
2	SHELL	NOTE 1	NOTE 4	1	700-1000-1								
1	BODY WITH BARREL	NOTE 1	NOTE 4	1	700-1112A2-1-16								
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A	ANGELA	DATE	05-06-'11	
DRAWING NO. 700-1112A2-16-50												FILE NO. R:\D\G\DWG\700\1112A2\16\50-1	