



REMARK: NO.2 MUST TURN AND SLIDE WITHOUT BINDING AND MUST BE CAPABLE OF WITHSTANDING A PULL-OFF FORCE OF 30 LBS. MIN. AFTER FORMING  
(NO.2 成型後可自由轉動和移動且至少需承受 30 LBS. 的拉力)

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)  
 1. BRASS  
 2. PHOSPHOR BRONZE  
 3. GOLD PL. 3 MIN. THICK OVER COPPER PL. 50 MIN. THICK  
 4. ALBALOY (COPPER-TIN-ZINC) PL. 80 MIN. THICK  
 5. TEFLON

1. CRIMPED FERRULE  
 HEX CRIMP SIZE .213"  
 2. CONTACT PIN TO SOLDER

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A		
7	FERRULE	NOTE 1	NOTE 4	1	FR-56-635-127	DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4					
6	COVER	NOTE 1	NOTE 4	1	CV-50-05						
5	CONTACT	NOTE 1	NOTE 3	1	700-1112A1-5						
4	INSULATOR	NOTE 5	NATURAL	1	700-1112A1-4T						
3	OUTER CONTACT	NOTE 2	NOTE 4	1	700-1000-2						
2	SHELL	NOTE 1	NOTE 4	1	700-1000-1	PART NO.					
1	BODY WITH BARREL	NOTE 1	NOTE 4	1	700-1112A1-1-07	APPROVED		DATE	05-27-'11	TITLE	QMA R/A CRIMP PLUG (FOR RG-223, 55, 142, 400)
						CHECKED		DATE	05-27-'11	DRAWING NO.	700-1112A1-07-50
						DRAWN		DATE	05-27-'11	FILE NO.	R:\D\G\DWG\700\1112A1\07\50-1