



SPECIFICATIONS :

- 1.IMPEDANCE : 50 OHMS
- 2.GOLD:3 microinches OVER BRASS(BODY)
- 3.GOLD:30 microinches OVER BRASS(CONTACT)
- 4.REMOVED ALL BURRS & BREAK ALL SHARP EDGES

8	r/ring	101-M000-R0-SX	1	SUS304	NONE
7	gasket	101-M000-M0-MX	1	S.I.R	RED
6	shell	101-M000-H0-BA	1	BRASS	GOLD
5	dielect	101-M111-70-DX	1	PTFE	NONE
4	dielect	152-A020-70-DX	1	PTFE	NONE
3	contact	152-A030-40-AC	1	BeCu	GOLD
2	body	101-A191-20-BA	1	BRASS	GOLD
1	body	152-A020-10-BA	1	BRASS	GOLD
ITEM	DESCRIPTION	PART NUMBER	QTY	MATERIAL	FINISH

REV	ECN NO.	NAME	DATE	TOLERANCE: DECIMALS: .XX ± 0.08 .X ± 0.13 DIAMETER: ± 0.03	皇亮精密企業股份有限公司 HUANG LIANG PRECISION ENTERPRISE CO., LTD				
A		CHEN	95/11/09		TITLE: QMA JACK TO SMA PLUG ADAPTER				
Drawn <i>CHEN</i> 95/11/09				Checked <i>CHEN</i> 95/11/09	Approved <i>H.T.LAN</i> 95/11/09	Unit mm	DWG.NO. 152-A030/111		
File Path:E:\CONNECTOR\QMA				A4	SCALE 5/1	SHEET 1 OF 1	SERIES QMA		